



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date: 2006/01/25

Product Name: 44MHz IF SAW Filter (BW=6.5 MHz)

TST Parts No.: TB0364A

Customer Parts No.: _____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Andy Yu

Approval by: _____ Francis Chen

Date: _____ 2006/10/05



TAI-SAW TECHNOLOGY CO., LTD.

No.3, Industrial 2nd Rd., Ping-Chen Industrial District, Taoyuan, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales3@mail.taisaw.com Web: www.taisaw.com


SAW Filter 44MHz (SMD 13.3×6.5 mm)

Model No.: TB0364A

Rev. No.:2.0

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. Operating Temperature: -40°C to +85°C
3. Storage Temperature: -40°C to +85°C




B. Characteristics :


Item	Unit	Min.	Type.	Max.
Center frequency, Fc	MHz	-	44	-
Insertion Loss, IL	dB	-	11.5	16
3 dB Bandwidth	MHz	6.5	6.8	
Pass band Ripple Fc±2.7MHz	dB	-	0.9	1.2
Stopband Rejection (ref: Max IL)				
Relative Attenuation Fc±3.6MHz	dB	4	6	
Relative Attenuation Fc±4.0MHz	dB	14	16	
Relative Attenuation Fc±7.0MHz	dB	40	46	
Relative Attenuation 26.5MHz to 37MHz	dB	40	58	
Relative Attenuation 51MHz to 61.5MHz	dB	40	42	

C. Frequency Characteristics :


(1) Frequency Response



(2) Passband response and Group Delay Variation:



D. Outline Drawing:



Pin K=L: RF input

Pin E=F: RF output

Pin A, B, C, D, G, H, I, J: To be Ground

□ : Week Code (Follow the table from planner each year)

Unit : mm

△ : Product / Year Code

Year	2005 2009	2006 2010	2007 2011	2008 2012
Product Code	B	b	<u>B</u>	<u>b</u>

H. Recommended Reflow Profile:

