

TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:


Product Name: 61.38MHz IF SAW Filter (BW=1.8MHz)

TST Parts No.: TB0728A

Customer Parts No.: _____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: Andy Yu *Andy*

Approval by: Francis Chen 

Date: 2009/03/10



TAI-SAW TECHNOLOGY CO., LTD.

No.3, Industrial 2nd Rd., Ping-Chen Industrial District, Taoyuan, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales3@mail.taisaw.com Web: www.taisaw.com


SAW Filter 61.38MHz (SMD 13.3×6.5 mm)

Model No.: TB0728A

Rev. No.:1.0

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. Operating Temperature: -20°C to +80°C
3. Storage Temperature: -40°C to +85°C




B. Characteristics :

Ambient Temperature: 25 °C


Item	Unit	Min.	Type.	Max.
Center frequency, F_c	MHz	-	61.38	-
Insertion Loss, IL	dB	-	8.8	10.0
-1 dB Bandwidth	MHz	1.8	2.53	-
-3 dB Bandwidth	MHz	2.8	2.98	-
-40 dB Bandwidth	MHz	-	4.92	5.2
Amplitude Ripple F_c±0.75MHz	dB	-	0.5	1.0
Group-delay Ripple F_c±0.75MHz	dB	-	110	150
Relative Attenuation 1.0 ~ 57.38MHz	dB	45	52	-
Relative Attenuation 65.38 ~150MHz	dB	45	48	-
Temp Coefficient	ppm/K	-23		

C. Frequency Characteristics :


(1) wide band Response:(span 50MHz)




(2) Pass band Response and Group Delay Variation: (span 5MHz)




(3) S11 Smith-Chart: (span 50MHz)






(4) S22 Smith-Chart: (span 50MHz)



(5) wide band Response:(span 150MHz)



D. Outline Drawing:



Pin K : RF Input

Pin E : RF Output

Pin A,B,C,D,F,G,H,I,J,L : Ground


Unit: mm

□ : Week Code (Follow the table from planner each year)


△ : Product / Year Code

Year	2005 2009	2006 2010	2007 2011	2008 2012
Product Code	B	b	<u>B</u>	<u>b</u>

E. PCB Footprint:



F. Matching Circuit:




$$Z_{in} = Z_{out} = 50 \text{ ohm}$$


$$L1 = 180\text{nH}, C1 = 110\text{pF}, L2 = 82\text{nH}, L3 = 220\text{nH}$$

G. Packing:

(1). REEL DIMENSION:



(2). TYPE DIMENSION:



H. Recommended Reflow Profile:

