



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specification Approval Sheet


Product Name: SAW Filter 159.1625MHz SMD 7.0x5.0 mm (BW=5.725MHz)

TST Parts No.:TA0395C

Customer Parts No.:_____

Customer signature required
Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Anne Chen 

Approved by: _____ Bob Chau 

Date: _____ 02, 22, 2016

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the change



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 159.1625 MHz

MODEL NO.: TA0395C

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 20 dB_m
2. DC voltage: 5 V
3. Operating Temperature: -40°C to +105°C
4. Storage Temperature: -40°C to +105°C

RoHS Compliant
Lead free
Lead-free soldering


Electrostatic Sensitive Device (ESD)

B. ELECTRICAL CHARACTERISTICS:



Item		Specification				
		Unit	Min.	Typ.	Max.	
Center Frequency	Fc	MHz	-	159.1625	-	
Insertion Loss	156.3~162.025MHz	IL	dB	-	2.3	3.8
Attenuation (Reference from 0dB)						
Fc-50 ~ Fc-30	MHz	dB	42	57	-	
Fc-30 ~ Fc-15	MHz	dB	36	55	-	
Fc+30 ~ Fc+50	MHz	dB	42	55	-	
Source impedance	Zs	Ω	-	50	-	
Load impedance	ZL	Ω	-	50	-	

C. MEASUREMENT CIRCUIT:


HP Network analyzer



D. Frequency Characteristics :



E.OUTLINE DRAWING:



Marking name : **395**

△ : year code : See the table

□ : Week Code. (Follow the table from planner each year)

Product Year Code

Year	2013 2017	2014 2018	2015 2019	2016 2020
Product Code	A	a	A	a

Pin configuration:

7: Input

2: Output

1,3,4,5,6,8,9,10: Ground


□ : Date Code

Unit: mm

□ Data code : See the table

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z


F. PCB Footprint :




G. PACKING:

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 245~260°C peak (min. 10sec).
4. Time : 2 times.

